





FOCUS


Design: Ronni Gol



FOCUS 1



FOCUS 2



FOCUS 2

FOCUS - 3000 K

Design: Ronni Gol

LIGHT·POINT
C O P E N H A G E N

ART. NAME	FOCUS 1	FOCUS 2	FOCUS 3
Art. no. white	261602	261608	261614
Art. no. black	261603	261609	261615
EAN white	5711389506025	5711389616083	5711389616144
EAN black	5711389451035	5711389616090	5711389616151
Material	Aluminium / Glass	Aluminium / Glass	Aluminium / Glass
Light source	Lumens	Lumens	Lumens
Lifetime	50.000	50.000	50.000
Number of light sources	1	2	3
Electronical gear	N/A	N/A	N/A
Driver watt	N/A	N/A	N/A
Light source watt	6	6	6
System watt	6	12	18
Voltage	220-240V	220-240V	220-240V
Dimmable	Leading/trailing Edge	Leading/trailing Edge	Leading/trailing Edge
Lumen output	540	1080	1620
Lumen pr. watt	90	90	90
Flux	415	830	1245
CCT (K)	3000	3000	3000
RA/CRI	≥90	≥90	≥90
Mac Adam	3	3	3
Light distribution	Direct	Direct	Direct
Beaming angle	20	20	20
Tilt angle	90	90	90
Cut out mm.	N/A	N/A	N/A
Rotation	350	350	350
Looping	Yes	Yes	Yes

FOCUS - 2700 K

Design: Ronni Gol

LIGHT·POINT
C O P E N H A G E N

ART. NAME	FOCUS 1	FOCUS 2	-
Art. no. white	270020	270030	-
Art. no. black	270021	270031	-
EAN white	5711389700201	5711389700300	-
EAN black	5711389700218	5711389700317	-
Material	Aluminium / Glass	Aluminium / Glass	-
Light source	Lumens	Lumens	-
Lifetime	50.000	50.000	-
Number of light sources	1	2	-
Electronical gear	N/A	N/A	-
Driver watt	N/A	N/A	-
Light source watt	6	6	-
System watt	6	12	-
Voltage	220-240V	220-240V	-
Dimmable	Leading/trailing Edge	Leading/trailing Edge	-
Lumen output	540	1080	-
Lumen pr. watt	90	90	-
Flux	415	830	-
CCT (K)	3000	3000	-
RA/CRI	≥90	≥90	-
Mac Adam	3	3	-
Light distribution	Direct	Direct	-
Beaming angle	38	38	-
Tilt angle	90	90	-
Cut out mm.	N/A	N/A	-
Rotation	350	350	-
Looping	Yes	Yes	-